

Starter Pack technical sheet



This is the basic solution to start your My Water Manager system. It consists of a box and two Dn20 modules, the first for the water inlet and the second for the hot water outlet.

Model		AquaManager 20	ConnectManager
Item number		1 4 3 0 2 2 2 0	1 1 2 4 3 3 1 4
Characteristics and performance			
Diameter connection	Dn	20	/
Water inlet connection	Inch	Louse nut 3/4	/
Water outlet connection	Inch	Male thread 3/4	/
Suitable for	Dn	10, 15, 20, 25	/
Minimum flow detection	Litre/minute	0,05	/
Maximum flow detection	Litre/minute	60	/
Minimum operating pressure	Bar	0,2	/
Maximum allowable pressure	Bar	10	/
Ambient operating temperature	°c	0° à 60°	/
Water temperature	°c	2° à 80°	/
Electrical data			
Power supply	Ph-V-Hz	Power supply via electrical outlet	Power supply via electrical outlet
Waterproofing	Class	IP65	/
Wifi standards		/	802.11 b/g/n/oc
Local network connectivity		/	One Ethernet port RJ45
Size / weight			
Product size	mm	240 – 160 – 49	187 – 84,5 – 37,8
Product weight	Kg	3,06	
Packaging size	mm	540 – 280 – 65	